RAFTER SPAN TABLES ALLOWABLE SPANS IN FEET AND INCHES

#2 Spruce-Pine-Fir

Nominal Size	O.C.	GROUND SNOW LOAD	GROUND SNOW LOAD
		=30psf Ceiling Not	=30PSF CEILING
		ATTACHED.	ATTACHED.
		DEAD LOAD =10PSF	DEAD LOAD =10PSF
	12"	9-1	8-3
2 X 4	16"	8-2	7-6
	24"	6-8	6-6
	12"	13-9	12-11
2 X 6	16"	11-11	11-9
	24"	9-9	9-9
	1		-
2 X 8	12"	17-5	17-0
	16"	15-1	15-1
	24"	12-4	12-4
2 X 10	12"	21-4	21-4
	16"	18-5	18-5
	24"	15-1	15-1
2 X 12	12"	24-8	24-8
	16"	21-5	21-5
	24"	17-6	17-6

Only with ceiling joists located near the base of the rafter at the bearing wall (1/7.5 or less)

RAFTER SPAN TABLES ALLOWABLE SPANS IN FEET AND INCHES

#2 Spruce-Pine-Fir

Nominal Size	O.C.	GROUND SNOW LOAD	GROUND SNOW LOAD
		=30psf Ceiling <i>Not</i>	=30psf Ceiling
		ATTACHED.	ATTACHED.
		DEAD LOAD =20PSF	DEAD LOAD =20PSF
	12"	8-5	8-3
2 X 4	16"	7-3	7-3
	24"	5-11	5-11
	12"	12-4	12-4
2 X 6	16"	10-8	10-8
	24"	8-8	8-8
2 X 8	12"	15-7	15-7
	16"	13-6	13-6
	24"	11-0	11-0
2 X 10	12"	21-4	21-4
	16"	18-5	18-5
	24"	15-1	15-1
	<u> </u>		
2 X 12	12"	22-1	22-1
	16"	19-2	19-2
	24"	15-7	15-7

CALCULATIONS REFERENCED TO ICC 2018 TABLES R802.4.1 (3) & 802.4.1 (4)